

cat. no. 103.08

Glazing of partition panels

X-RAY GLAZING OF PARTITION PANELS



X-ray glazing of partition panels is yet another element, together with partitions and doors, to construct clean workplaces and areas with protection against X-radiation. Its design makes it suitable especially for hospital environments, different areas in pharmaceutical industry, electrical engineering industry, mechanical engineering industry, food industry, etc.

MORE INFORMATION, PHOTOS



TECHNICAL DATA

Type
RTG window panel - Pharma glazing across panel width
Panel thickness
100 mm
120 mm
60 mm
80 mm

Structural opening dimensions

width	height
1190 mm	1000 mm
1190 mm	800 mm

Maximum structural opening dimensions 1190x1000x120 mm!
Minimum structural opening dimensions 640x800x60 mm.
Panels of different width must be made as atypical (max. panel width is 1190 mm).
Min. width 560 mm, max. dimension 1190 mm. Min. height 800 mm, max. dimension 1000 mm.

Glazing

glazing equivalent to 1 mm of lead
glazing equivalent to 1.5 mm of lead
glazing equivalent to 2 mm of lead
atypical

Blinds type

without blinds
atypical
magnetic blinds
mechanical blinds

Blinds control

on visible side
on non-visible side
on both sides

Attention: Magnetic blinds can be controlled only from one side! Standard hue of blinds S156 according to the manufacturer's sample book, custom hues according to RAL colour standard. The notes must specify the number of the panel in which the blinds control will be installed.

Hue and material

metal sheet, hue RAL 9002
metal sheet, hue RAL 9016
Stainless steel AISI 304 FIN 8
Komaxit, hue RAL

Attention: Magnetic blinds can be controlled only from one side! Standard hue of blinds S156 according to the manufacturer's sample book, custom hues according to RAL colour standard. The notes must specify the number of the panel in which the blinds control will be installed.

Atypical design

Type design
Atypical design
Type design
0 - Unique specification out of offered versions
Atypical design
Q - atypical design that cannot be uniquely specified by a code